

# Avatar Grove 12 Mil Specifications and Warranties

## General:

Description: Class: Wear Layer Thickness: Overall Thickness: Size: Finish: Installation: Recommended Adhesive:

## Packaging:

Square Feet / Carton: Pieces / Carton: Weight / Carton: Cartons / Pallet:

## Performance:

Slip Resistance: Dimensional Stability: Static Load: Flexibility: Heat Resistance: Light Resistance: Chemical Resistance: Indoor Air Quality:

### Flammability:

Radiant Flux: Smoke Density:

### Maintenance:

Routine Cleaning:

Luxury vinyl tile Class III printed film vinyl tile, Type B (embossed) 12 mil (.3mm) 2.5mm 6"W x 48"L Quartz enhanced urethane Direct glue Premium, high strength, spread or spray adhesive

42 sqft 21 pcs 35.4 lbs 48 cartons

ADA Compliant (ASTM D2047) less than .02"/ft (ASTM F2199) 750 psi (lbs/sqin) - .005" (ASTM F970) Pass (ASTM F137) Pass (ASTM F1514) Pass (ASTM F1515) Pass (ASTM F925) FloorScore certified

>.45 watts/cm<sup>2</sup>, NFPA Class I (ASTM 648) Pass <450 (ASTM E662)

Sweep, vacuum, or dust mop. Add neutral pH cleaner to cool water following manufacturer's recommendations. As needed, scrub with a low-rpm machine or auto scrubber using a red pad and neutral cleaner following manufacturer's instructions.

### Warranty:

7 Year Commercial Limited Warranty