

Avatar Grove 20 Mil Specifications and Warranties

General:

Description: Luxury vinyl tile

Class: Class III printed film vinyl tile, Type A (smooth) Type B

(embossed)

Wear Layer Thickness: 20 mil (.5mm)
Overall Thickness: 2.5mm
Size: 6"W x 48"L

Finish: Quartz enhanced urethane

Installation: Direct glue

Recommended Adhesive: Premium, high strength, spread or spray adhesive

Packaging:

Square Feet / Carton:42 sqftPieces / Carton:21 pcsWeight / Carton:35.4 lbsCartons / Pallet:48 cartons

Performance:

Slip Resistance: ADA Compliant (ASTM D2047)
Dimensional Stability: less than .02"/ft (ASTM F2199)
Static Load: 750 psi (lbs/sqin) - .005" (ASTM F970)

Flexibility:
Pass (ASTM F137)
Heat Resistance:
Pass (ASTM F1514)
Light Resistance:
Pass (ASTM F1515)
Chemical Resistance:
Pass (ASTM F925)
Indoor Air Quality:
FloorScore certified

Flammability:

Radiant Flux: >.45 watts/cm², NFPA Class I (ASTM 648)

Smoke Density: Pass <450 (ASTM E662)

Maintenance:

Routine Cleaning: Sweep, vacuum, or dust mop.

Add neutral pH cleaner to cool water following

manufacturer's recommendations.

As needed, scrub with a low-rpm machine or auto scrubber using a red pad and neutral cleaner following manufacturer's

instructions.

Warranty:

10 Year Commercial Limited Warranty