

## Cradle Mountain 12 Mil Specifications and Warranties

General:

Description: Luxury vinyl tile

Class: Class III printed film vinyl tile, Type A (smooth) Type B

(embossed)

Wear Layer Thickness: 12 mil (.3mm)

Overall Thickness:2 mmSize:6"W x 36"LFinish:UrethaneInstallation:Direct glue

Recommended Adhesive: Premium, high strength, spread or spray adhesive

Packaging:

Square Feet / Carton:53.48 sqftPieces / Carton:36 pcsWeight / Carton:40.7 lbsCartons / Pallet:48 cartons

Performance:

Slip Resistance: ADA Compliant (ASTM D2047)
Dimensional Stability: less than .02"/ft (ASTM F2199)
Static Load: 750 psi (lbs/sqin) - .005" (ASTM F970)

Flexibility: Pass (ASTM F137)
Heat Resistance: Pass (ASTM F1514)
Light Resistance: Pass (ASTM F1515)
Chemical Resistance: Pass (ASTM F925)
Indoor Air Quality: FloorScore certified

Flammability:

Radiant Flux: >.45 watts/cm², NFPA Class I (ASTM 648)

Smoke Density: Pass <450 (ASTM E662)

Maintenance:

Routine Cleaning: Sweep, vacuum, or dust mop.

Add neutral pH cleaner to cool water following

manufacturer's recommendations.

As needed, scrub with a low-rpm machine or auto scrubber using a red pad and neutral cleaner following manufacturer's

instructions.

Warranty:

7 Year Commercial Limited Warranty