

Fresh Start MCL 40 Specifications and Warranties

General:

Description: Dye Method: Fiber: Tufted Face Weight: Gauge: Pile Height: Primary Backing: Secondary Backing: Anti-Stain and Soil Protection: Antimicrobial Treatment: Broadloom Width: Origin:

Performance:

Static Electricity: Traffic: Indoor Air Quality:

Flammability:

Radiant Panel: Smoke Density: Methenamine Pill Test:

Maintenance:

Spot Cleaning:

Professional Cleaning:

Warranties:

15 Year Limited Abrasive Wear 15 Year Limited Texture Retention Lifetime Stain Resistance Lifetime Soil Resistance Lifetime Limited Antistatic Protection 2-Year Limited Manufacturing Defects Multi-level cut & loop broadloom carpet Injection dyed 100% Invista Stainmaster® Tactesse® Type 6,6 Nylon 40 oz. / sq.yd. 1/10th .44 in. Woven polypropylene Endura-Loc™ Dupont Advanced Teflon® Protectant AlphaSan® built-in protection 13'6 U.S.A.

< 3.5 KV (AATCC-134) Permanent conductive fiber Residential Green Label Plus Certified

> 0.45 watts/cm2 (ASTM – E648, Class I)
< 450 flaming and non-flaming (ASTM-E662 NFPA-258)
Self-extinguishing (CPSC FF-1-70)

Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly. Hot water extraction