

Marathon Cut 26 Specifications and Warranties

General:

Description: Dye Method: Dye Resolution: Fiber: Tufted Face Weight: Tuft Bind: Gauge: Pile Height: Primary Backing: Delamination: Anti-Soil and Stain Protection: Antimicrobial Protection: Broadloom Width: Origin:

Performance:

Static Electricity: Traffic: Indoor Air Quality:

Flammability:

Radiant Panel: NBS Smoke Chamber:

Maintenance:

Spot Cleaning:

Professional Cleaning:

Commercial Limited Warranties:

20 Year 10% Fiber Loss Abrasive Wear Warranty
20 Year Texture Retention Warranty
10 Year Soil and Stains Warranty
Lifetime Antistatic Warranty
10 Year Tuft Bind Warranty
Fade Resistance (for indoor use only)

Cut pile broadloom **Digital dye injection** 256 dpi **Premium BCF Type 6 Nylon** 26 oz / sqyd Exceeds industry standards 1/10th .193 in. Woven polypropylene ActionBac Exceeds industry standards **Integrated soil and stain treatment Integrated mold, mildew, and odor treatment** 12' U.S.A.

< 3.5 KV (AATCC-134) Residential or commercial use



Green Label Plus[®] Certifies product exceeds most stringent indoor air quality standards and are best suited for living, working, and learning environments

1.08 watts/cm2 (ASTM – E648, Class I) < 450 flaming and non-flaming (ASTM-E662 NFPA-258)

Spot clean with approved carpet cleaner. Follow label directions Vacuum regularly Hot water extraction

- Abrasive wear of surface pile guaranteed not to exceed 10%
- Guaranteed to maintain appearance under heavy foot traffic
- Provides total fiber protection against soil and stains
- Built-in static control fiber
- Guaranteed to maintain superior tuft bind in high traffic areas
- Resists fading under normal indoor use

