



Joy Carpets & Co.

WEATHERGUARD™ SPECIFICATIONS AND WARRANTIES

	First Steps™	Concierge™	Promenade™	Corporate Image™
Description	Modular entrance matting	Modular entrance matting	Walk off mat	Walk off mat
Tile Construction	UV resistant PVC	UV resistant PVC with fabric insert	n/a	n/a
Tile Color	Graphite	Graphite	n/a	n/a
Tile Size (L x W x H)	8.25" x 8.25" x .375"	8.25" x 8.25" x .375"	n/a	n/a
Tile Size In Use (L x W x H)	7.75" x 7.75" x .375"	7.75" x 7.75" x .375"	n/a	n/a
Fabric Construction	n/a	Tufted Cut Pile	Tufted Cut Pile	Tufted Cut Pile
Face Fiber	n/a	Twisted, heat set type 6,6 nylon	Twisted, heat set type 6,6 nylon	Twisted, heat set type 6,6 nylon
Dye Method	n/a	Injection dyed	Solution dyed	Injection dyed
Backing	n/a	n/a	Nitrile rubber with gripper cleats	Nitrile rubber with gripper cleats
Mat Profile	n/a	n/a	.45"	.33"
Tufted Face Weight	n/a	n/a	19 oz. / sqyd	21 oz. / sqyd
Antistatic	n/a	n/a	Yes	Yes
Antistain/Antisoil Treatment	n/a	n/a	Yes	KMT™
Border Width	n/a	n/a	.625"	.75"
Fade Resistant	Yes	Yes	Yes	Yes
Bleach Resistant	Yes	No	Yes	No
Installation	SnapTite™ interlocking system	SnapTite™ interlocking system	n/a	n/a
Flammability	Low radius of effect of ignition (BS 4790)	Low radius of effect of ignition (BS 4790)	Pass (DOC FF1, FF2 -70)	Pass (DOC FF1, FF2 -70)
Wear Resistance	Vetterman 22,000 cycles	Vetterman 22,000 cycles	n/a	n/a
Maintenance	Vacuum regularly. Pressure wash	Vacuum regularly. Wet extraction*	Vacuum regularly. Machine wash.	Vacuum regularly. Machine wash.
Manufacturer Defects Warranty	1 year	1 year	1 year	1 year
Wear Warranty	5 years	5 years	5 years	5 years
Surface-mount, tapered edging system for First Steps™ and Concierge™				
Construction	UV resistant PVC			
Color	Graphite			
Length	15.75"			
Installation	SnapTite™ interlocking system			

*Water temp to not exceed 50 degrees Celcius

Specifications are subject to normal manufacturing tolerance.

Sizes are approximate and carpet color may vary.