



Joy Carpets & Co.

Higher Calling Specifications and Warranties

General:

Description:	Multi-level patterned loop carpet tile
Dye Method:	Solution dyed
Fiber:	BCF Type 6 2-ply premium nylon
Face Weight:	16 oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/12 th
Pile Height:	.10 in.
Total Height:	.23 in.
Backing:	Echelon® composite backing
Delamination:	Exceeds industry standards
Anti-Soil and Stain Protection:	Impervion® soil and stain treatment
Tile Size:	9" x 36"
Origin:	USA
Installation Method:	Ashlar, monolithic, quarter-turn, random

Performance:

Static Electricity:	< 3.5 KV (AATCC-134), Permanent Conductive Fiber
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified

Flammability:

Radiant Panel:	> 0.45 watts/cm ² (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (DOC FF-1-70)

Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction

Warranties:

Lifetime Face Fiber Wear
Lifetime Soil and Stain Protection
Lifetime Edge Ravel
Lifetime Delamination of Backing
Lifetime Dimensional Stability
Lifetime Tuft Bind
Lifetime Tuft Bind
Lifetime Colorfastness
Lifetime Antistatic Protection