

## Trinity Specifications and Warranties

General:

Description: Multi-level patterned loop carpet tile

Dye Method: Solution dyed

Fiber: BCF Type 6 2-ply premium nylon

Face Weight: 17 oz. / sq. yd.

Tuft Bind: Exceeds industry standards

Gauge: 1/12<sup>th</sup>
Pile Height: .10 in.
Total Height: .22 in.

Backing: Echelon® composite backing
Delamination: Exceeds industry standards

Anti-Soil and Stain Protection: Impervion® soil and stain treatment

Tile Size: 18" x 36"
Origin: USA

Installation Method: Ashlar, monolithic, herringbone, basketweave, stagger, offset

Performance:

Static Electricity: < 3.5 KV (AATCC-134), Permanent Conductive Fiber

Traffic: Heavy commercial use Indoor Air Quality: Green Label Plus Certified

Flammability:

Radiant Panel: > 0.45 watts/cm2 (ASTM – E648, Class I)

NBS Smoke Chamber: < 450 (ASTM-E662 NFPA-258)
Methenamine Tablet: Self-extinguishing (DOC FF-1-70)

Maintenance:

Spot Cleaning: Spot clean with approved carpet cleaner. Follow

manufacturer recommendations. Vacuum regularly.

Professional Cleaning: Hot water extraction

Warranties:

Lifetime Face Fiber Wear

Lifetime Soil and Stain Protection

Lifetime Edge Ravel

Lifetime Delamination of Backing

Lifetime Dimensional Stability

Lifetime Tuft Bind Lifetime Tuft Bind

Lifetime Colorfastness

Lifetime Antistatic Protection