

## Cradle Mountain 20 Mil Specifications and Warranties

General:

Description: Luxury vinyl tile

Class: Class III printed film vinyl tile, Type A (smooth) Type B

(embossed)

Wear Layer Thickness: 20 mil (.5mm)
Overall Thickness: 2.5 mm
Size: 6"W x 36"L

Finish: Quartz Enhanced Urethane

Installation: Direct glue

Recommended Adhesive: Premium, high strength, spread or spray adhesive

Packaging:

Square Feet / Carton:44.56 sqftPieces / Carton:30 pcsWeight / Carton:39.1 lbsCartons / Pallet:48 cartons

Performance:

Slip Resistance: ADA Compliant (ASTM D2047)
Static Load: 2000 psi (lbs/sqin) (ASTM F970)

Flexibility:

Pass (ASTM F137)

Heat Resistance:

Pass (ASTM F1514)

Light Resistance:

Pass (ASTM F1515)

Chemical Resistance:

Pass (ASTM F925)

Fungal Resistance:

Pass (ASTM G21)

Bacterial Resistance:

Pass (AATCC 147)

Indoor Air Quality:

FloorScore certified

Flammability:

Radiant Flux: >.45 watts/cm², NFPA Class I (ASTM 648)

Smoke Density: Pass <450 (ASTM E662)

Maintenance:

Routine Cleaning: Sweep, vacuum, or dust mop.

Add neutral pH cleaner to cool water following

manufacturer's recommendations.

As needed, scrub with a low-rpm machine or auto scrubber using a red pad and neutral cleaner following manufacturer's

instructions.

Warranty:

10 Year Commercial Limited Warranty