



Joy Carpets & Co.

Rough Rider Cut 32 Specifications and Warranties

General:

Description:	Cut pile broadloom
Dye Method:	Injection dyed
Dye Resolution:	400 dpi
Fiber:	BCF Type 6,6 2-Ply Premium Nylon
Tufted Face Weight:	32oz. / sq. yd.
Tuft Bind:	Exceeds industry standards
Gauge:	1/10 th
Pile Height:	.22 in.
Primary Backing:	Woven polypropylene
Secondary Backing:	ActionBac
Secondary Backing (optional):	KangaTRAC polyurethane cushion
Delamination:	Exceeds industry standards
Anti-Stain Protection:	Impervion® soil and stain treatment
Broadloom Width:	13'6
Origin:	U.S.A.

Performance:

Static Electricity:	< 3.5 KV (AATCC-134)
Traffic:	Heavy commercial use
Indoor Air Quality:	Green Label Plus Certified

Flammability:

Radiant Panel:	> 0.45 watts/cm ² (ASTM – E648, Class I)
NBS Smoke Chamber:	< 450 flaming and non-flaming (ASTM-E662 NFPA-258)
Methenamine Tablet:	Self-extinguishing (DOC FF-1-70)

Maintenance:

Spot Cleaning:	Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly.
Professional Cleaning:	Hot water extraction.

Warranties:

- 10 Year 10% Fiber Loss Wear Warranty
- 10 Year Soil and Stain Protection Limited Warranty
- 10 Year Atmospheric Fading Warranty
- 10 Year Antistatic Warranty
- 10 Year Delamination of Backing Warranty
- 10 Year Tuft Bind Warranty