

Wall Street Specifications and Warranties

General:

Description: Dye Method: Dye Resolution: Fiber: Total Weight: Tuft Bind: Gauge: Pile Height: Backing: Delamination: Anti-Soil and Stain Protection: Tile Size: Origin:

Performance:

Static Electricity: Traffic: Indoor Air Quality:

Flammability:

Radiant Panel: NBS Smoke Chamber: Methenamine Tablet:

Maintenance:

Spot Cleaning:

Professional Cleaning:

Warranties:

Lifetime Face Fiber Wear Lifetime Soil and Stain Protection Lifetime Edge Ravel Lifetime Antistatic Protection Lifetime Floor Compatibility Lifetime Floor Release Lifetime Moisture Resistance Textured loop pile carpet tile Injection dyed 400 dpi BCF Type 6,6 2-Ply Premium Nylon 114 oz. / sq. yd. Exceeds industry standards 1/10th .27 in. StayTac[®] cushion – PVC free. No adhesives required Exceeds industry standards Impervion[®] soil and stain treatment 1m x 1m (39.4" x 39.4") U.S.A.

< 3.0 KV (AATCC-134), Permanent Conductive Fiber Severe commercial use Green Label Plus Certified

> 0.45 watts/cm2 (ASTM – E648, Class I)
< 450 (ASTM-E662 NFPA-258)
Self-extinguishing (DOC FF-1-70)

Spot clean with approved carpet cleaner. Follow manufacturer recommendations. Vacuum regularly. Hot water extraction

Lifetime Tuft Bind Lifetime Color Pattern Permanency Lifetime Cushion Resiliency Lifetime Delamination Lifetime Dimensional Stability