



Joy Carpets & Co.

Applewood Specifications and Warranties

General:

Description:	Luxury vinyl plank
Class:	Class III printed film vinyl tile, Type B (embossed)
Wear Layer Thickness:	28 mil (.7mm)
Overall Thickness:	2.5mm
Size:	5"W x 48"L
Finish:	Adamas UV-Cured Polyurethane
Edge Profile:	Micro bevel
Installation:	Direct glue
Recommended Adhesive:	Premium, high strength, spread or spray adhesive

Packaging:

Square Feet / Carton:	35 sqft
Pieces / Carton:	21 pcs
Weight / Carton:	29 lbs

Performance:

Slip Resistance:	Pass (ASTM D2047)
Dimensional Stability:	Pass (ASTM F2199)
Static Load:	Pass (ASTM F970)
Flexibility:	Pass (ASTM F137)
Heat Resistance:	Pass (ASTM F1514)
Light Resistance:	Pass (ASTM F1515)
Chemical Resistance:	Pass (ASTM F925)
Indoor Air Quality:	FloorScore certified

Flammability:

Radiant Flux:	Pass - Class I (ASTM 648)
Smoke Density:	Pass <450 (ASTM E662)

Maintenance:

Routine Cleaning:	Sweep, vacuum, or dust mop. Add neutral pH cleaner to cool water following manufacturer's recommendations. As needed, scrub with a low-rpm machine or auto scrubber using a red pad and neutral cleaner following manufacturer's instructions.
-------------------	--

Warranty:

12 Year Commercial Limited Warranty
1 Year Manufacturing Defect Warranty