

Slate Specifications and Warranties

General:

Description: Luxury vinyl plank

Class III printed film vinyl tile, Type B (embossed)

Wear Layer Thickness: 28 mil (.7mm)
Overall Thickness: 2.5mm
Size: 18"W x 18"L

Finish: Adamas UV-Cured Polyurethane

Edge Profile: Micro bevel Installation: Direct glue

Recommended Adhesive: Premium, high strength, spread or spray adhesive

Packaging:

Square Feet / Carton:36 sqftPieces / Carton:16 pcsWeight / Carton:30 lbs

Performance:

Slip Resistance: Pass (ASTM D2047) **Dimensional Stability:** Pass (ASTM F2199) Static Load: Pass (ASTM F970) Flexibility: Pass (ASTM F137) Heat Resistance: Pass (ASTM F1514) Light Resistance: Pass (ASTM F1515) Chemical Resistance: Pass (ASTM F925) Indoor Air Quality: FloorScore certified

Flammability:

Radiant Flux: Pass - Class I (ASTM 648) Smoke Density: Pass <450 (ASTM E662)

Maintenance:

Routine Cleaning: Sweep, vacuum, or dust mop.

Add neutral pH cleaner to cool water following

manufacturer's recommendations.

As needed, scrub with a low-rpm machine or auto scrubber using a red pad and neutral cleaner following manufacturer's

instructions.

Warranty:

12 Year Commercial Limited Warranty 1 Year Manufacturing Defect Warranty