

# Travertine Specifications and Warranties

## General:

Description: Class: Wear Layer Thickness: Overall Thickness: Size: Finish: Edge Profile: Installation: Recommended Adhesive:

# Packaging:

Square Feet / Carton: Pieces / Carton: Weight / Carton:

## Performance:

Slip Resistance: Dimensional Stability: Static Load: Flexibility: Heat Resistance: Light Resistance: Chemical Resistance: Indoor Air Quality:

# Flammability:

Radiant Flux: Smoke Density:

### Maintenance:

Routine Cleaning:

Luxury vinyl plank Class III printed film vinyl tile, Type B (embossed) 28 mil (.7mm) 2.5mm 18"W x 18"L Adamas UV-Cured Polyurethane Micro bevel Direct glue Premium, high strength, spread or spray adhesive

36 sqft 16 pcs 30 lbs

Pass (ASTM D2047) Pass (ASTM F2199) Pass (ASTM F970) Pass (ASTM F137) Pass (ASTM F1514) Pass (ASTM F1515) Pass (ASTM F925) FloorScore certified

Pass - Class I (ASTM 648) Pass <450 (ASTM E662)

Sweep, vacuum, or dust mop. Add neutral pH cleaner to cool water following manufacturer's recommendations. As needed, scrub with a low-rpm machine or auto scrubber using a red pad and neutral cleaner following manufacturer's instructions.

### Warranty:

12 Year Commercial Limited Warranty 1 Year Manufacturing Defect Warranty